

DISPKIT-MINI

CTC Product Display Kit with Non-Functional Parts



Product Features

- ▶ Ten pieces of our most popular CTC Line products
- ▶ Durable, foam-lined plastic case (11.72 in. L x 8.00 in. W x 3.86 in. H)
- ▶ Allow your customers to experience the quality and durability of a wide assortment of CTC products

Accelerometers

- ▶ **Standard Size Sensor** *Side Exit*
- ▶ **Standard Size Sensor** *Top Exit*
- ▶ **Compact Size Sensor** *Top Exit*
- ▶ **Compact Size Sensor** *Triaxial*
- ▶ **Mini Size Sensor** *Top Exit*

Cables & Connectors

▶ CB111-V2N

<i>CB111 Cable</i>	<i>Twisted, Shielded Pair Cable, Yellow FEP Jacket, 0.19 in. (4.8 mm) OD, 392 °F (200 °C) Max Temp</i>
<i>V2N Connector</i>	<i>2 Socket MIL-Style, Seal-Tight Viton® Boot Connector with Nylon Insert, Permanent Mount, 250 °F (121 °C) Max Temp</i>

▶ CB206-A2A

<i>CB206 Cable</i>	<i>Low Cost, Twisted, Shielded Pair Cable, Lightweight Red FEP Jacket with Stainless Steel Outer Armor, 0.27 in. (6.9 mm) OD, 392 °F (200 °C) Max Temp</i>
<i>A2A Connector</i>	<i>2 Socket MIL-Style, Polycarbonate Molded Connector, Permanent Mount, 250 °F (121 °C) Max Temp</i>

Mounting Hardware

- ▶ **MH103-1B** *Flat Surface Magnet Mounting Base with 1/4-28 Integral Mounting Stud, 40 lbs. (18 kg) Pull Strength, 1.00 in. (25.4 mm) OD, 0.46 in. (11.68 mm) Height*
- ▶ **MH130-1A** *Adhesive Mounting Disk with 1/4-28 Blind Tapped Hole, 1.00 in. (25.4 mm) Diameter*
- ▶ **MH118-3A** *Motor Fin Mount Probe Pad, 0.25 in. x 1.75 in. (6.35 mm x 44.45 mm) Probe Tip*