



























Connector Kits for Field Installation

Part #	Installed Connector Side View	Connector Kit Parts	Connector Kit Parts #	Diameter	Max Temp.	Compatible Cables
CF-F		 Stock Product BNC Plug Connector Kit	CF-F	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111
CF-E		 Stock Product BNC Jack Connector Kit	CF-E	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111
CF-EMPP		 Stock Product BNC Jack Connector Kit	CF-EMPP	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB110, CB111, CB202, CB206 CB802, CB806 CB810, CB811
CF-G3H-250		 Stock Product 3 Socket Connector Kit	CF-G3H-250	≤.250" (6,4 mm)	250°F (121°C)	CB105, CB117 CB119, CB212
CF-G4H1-250		 Stock Product 4 Socket Connector Kit	CF-G4H1-250	≤.250" (6,4 mm)	250°F (121°C)	CB105, CB112 CB117, CB218
CC-J2A-175 CC-J2A-190 CC-J2A-250 CC-J2A-360		 Stock Product 2 Socket mini-MIL Connector Kit	CC-J2A-175 CC-J2A-190 CC-J2A-250 CC-J2A-360	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm) .360" (9,1 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103, CB206 CB102, CB103, CB110, CB111, CB202, CB206 CB802, CB806 CB810, CB811
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
CC-J4A-175 CC-J4A-190 CC-J4A-250 CC-J4A-360		 Stock Product 4 Socket mini-MIL Connector Kit	CC-J4A-175 CC-J4A-190 CC-J4A-250 CC-J4A-360	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm) .360" (9,1 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB119 CB105, CB218 CB105, CB117, CB119, CB218, CB819
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
CF-R2C-175 CF-R2C-190 CF-R2C-250		 Stock Product 2 Pin Connector Kit	CF-R2C-175 CF-R2C-190 CF-R2C-250	.175" (4,5 mm) .190" (4,8 mm) .250" (6,4 mm)	250°F (121°C) 250°F (121°C) 250°F (121°C)	CB102, CB110 CB111 CB103, CB206
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
CF-SF		 Stock Product 3 Pin/Socket Safety Feature Kit	CF-SF	.250" (6,4 mm)	250°F (121°C)	CB102, CB103 CB104, CB108, CB110, CB111
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
CF-SFT		 Stock Product 5 Pin/Socket Safety Feature Kit	CF-SFT	.250" (6,4 mm)	250°F (121°C)	CB105, CB112, CB119
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
CC-V2R		 Stock Product 2 Socket Viton Boot Connector Kit, High Temperature	CC-V2R	.190" (4,8 mm)	350°F (177°C)	CB111
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
CC-V3R		 Stock Product 3 Socket Viton Boot Connector Kit, High Temperature	CC-V3R	.190" (4,8 mm)	350°F (177°C)	CB119
<i>Supplied with epoxy and syringe (MH109-3A)</i>						
MH109-3A		 Stock Product For use with Field Installable Connector Kits Potting Adhesive, 10 g, with 10 ml Syringe	MH109-3A	N/A	392°F (200°C)	N/A



Backed by our Unconditional Lifetime Warranty

www.ctonline.com



VIBRATION ANALYSIS HARDWARE