

# Accelerometer Quick Disconnects

## MH107-4 Series Thru-Bolt Quick Disconnect MH107-6 Series Multi-Stud Mounting Kits (For M6 bolts)

Stock Product



CP101-4A Cap Cover

MH107-1A Receptacle

MH107-2B Stud with Thru-Bolt  
(M6 Size Also Available)

### Product Purpose

**Provides Convenient, Consistent Data Collection**

CTC's Accelerometer Quick Disconnects are ideally suited for triaxial sensor use. They feature a convenient locating notch and an easy, quarter-turn connection.

### Component Specifications

Broad Frequency Response	0-390,000 CPM (0-6500 Hz)
Rugged	Engages five threads in 1/4 turn
Corrosion Resistant	316L Stainless Steel
Easy To Install	Quick Disconnect Stud may be epoxied and/or stud mounted
90 Degree Engagement	For accurate, repeatable readings with triaxial accelerometers

### Ordering Information

All Products Listed Below Are Stock Products

Kit Part Number (1/4-28 Bolt)	Kit Part Number (M6 x 1 Bolt)	Receptacle	Studs, Screws and Cap Covers
MH107-4A	MH107-6A	2	50
MH107-4B	MH107-6B	3	100
MH107-4C	MH107-6C	4	200
MH107-4D	MH107-6D	6	300
MH107-4E	MH107-6E	10	500
MH107-4F	MH107-6F	20	1,000

## Probe Tips for Portable Measurements

### Product Purpose

**Probe Tips allow easy access to measurement points**

CTC's MH119 series probe tips connect directly to any standard 1/4-28 threaded accelerometer. Each Probe is made of tough 300 stainless steel to ensure long term survival in tough factory environments. Tips allow easy access to measurement points that are in difficult to reach areas such as cooling fins.



Part Number	Length (A)	Stock Product
MH119-1A	2.5 in. (63,5 mm)	Stock Product
MH119-2A	4.0 in. (101,6 mm)	Stock Product
MH119-3A	8.0 in. (203,2 mm)	Stock Product

### MH119 Series



Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com)

