

# Vibration Switch Kit - VSK2000

## Product Features

### Multi-Channel Vibration Switch

Component system allows for the accelerometer to be installed at the optimum measurement point, while the signal conditioner, relay and display can be adjusted for your application.

- PLC, DCS, SCADA connectivity
- 24/7 monitoring with shutdown alarm
- Field configurable, multi-channel
- Dynamic outputs for vibration analysis

*Cooling is required if internal temperature of RXE enclosure exceeds 140°F (60°C).*



## RXE150

### Vibration Protection & Relay System



**Build To Order**

- 24/7 protection for critical equipment for shutdown or alarm
- Accommodates up to four 4-20 mA signal conditioners and four relay units from remotely installed sensors
- For use with SC200 Series signal conditioners and RE200 Series relays (sold separately)

*Cooling is required if internal temperature of RXE enclosure exceeds 140°F (60°C).*

## AC192 & AC194 Series

### Compact, Multi-Purpose Accelerometer, 100 mV/g



**Build To Order**

- Accelerometers for analysis and process control
- Superior RF immunity
- $\pm 80g$  dynamic range,  $\pm 10\%$  sensitivity

## CB111-A2A

### Yellow Teflon® Jacketed Cable with 2 Socket MIL



**Build To Order**

Pin Out	Application	Conductors	Shield	Wire Gauge
A = Signal (+) B = Common (-)	Permanent Monitoring	2 Conductor Twisted & Shielded Pair	Braided Shield with Drain Wire	AWG = 20

**Please Consult The Factory For Options, or Our Part Configurator at [www.ctconline.com](http://www.ctconline.com)**

**Lifetime Warranty on Materials & Workmanship**

[www.ctconline.com](http://www.ctconline.com)