

	<b>FFv PROBE TIP (5mm diameter)</b>	<b>8mm PROBE TIP</b>	<b>11mm PROBE TIP</b>	<b>25mm PROBE TIP</b>
<b>PRO Model Number</b>	DP1009 Series	DP1001 Series	DP1007 Series	DP100851 Series
<b>Bently® Model Number</b>	3309 Series	33010 Series	3307 Series	3308 Series
<b>Linear Range</b>	10 to 70 mils (0.25mm to 1.75mm)	10 to 90 mils (0.25mm to 2.30mm)	20 to 180 mils (0.25mm to 4.57mm)	25 to 525 mils (0.635mm to 13.33mm)
<b>System Lengths</b>	5m or 7m	5m or 9m	5m or 9m	5m or 9m
<b>Sensitivity</b>	200 mV/mil (7.87 V/mm)	200 mV/mil (7.87 V/mm)	100 mV/mil (3.94 V/mm)	20 mV/mil (0.787 V/mm)
<b>Recommended Gap</b>	40 mils	50 mils	100 mils	275 mils
<b>Threaded Body Size</b>	1/4-28 M8x1	3/8-24 M10x1	1/2-20 M14x1.5	1 1/4-12 M30x2
<b>Common Applications</b>	Steam turbines, pumps, gear boxes, motors, fans, general purpose	Steam turbines, pumps, gear boxes, motors, fans, general purpose	Hydro turbines, large displacement machines, general purpose	Axial thrust and differential expansion, general purpose
<b>Eddy Current Field</b>				