

PROXIMITY PROBE COMPARISON

SPECIFICATIONS / FEATURES	COMPETITORS' PROXIMITY PROBES	PRO LINE PROXIMITY PROBES
WARRANTY	3 year limited warranty	Lifetime warranty on materials & workmanship
LEAD TIME	Months	Approximately 1 month
PROBE CASE MATERIAL	AISI 304 stainless steel	AISI 316L stainless steel
PROBE TIP RATING	Specialty probes needed	IP68
PROBE TIP PRESSURE RATING	Sealing material consists of a Viton® O-ring	Viton® O-ring seal tested to 100 PSI
CABLE JACKET	Tears through when pulling through conduit	Thicker cable jacket for increased durability when pulling through conduit
REVERSE MOUNT FFv PROBE OPTIONS	3/8-24 thread, M10x1 thread	1/4-24 thread, 3/8-24 thread, M8x1 thread, M10x1 thread
TEMPERATURE RATINGS	-51 °C to 177 °C (-60 °F to 350 °F)	-51 °C to 177 °C (-60 °F to 350 °F)
LINEAR RANGE 5 MM (FFv)	10 - 70 Mils (60 Mils)	10 - 70 Mils (60 Mils)
LINEAR RANGE 8 MM	10 - 90 Mils (80 Mils)	10 - 90 Mils (80 Mils)
LINEAR RANGE 11 MM	20 - 180 Mils (160 Mils)	20 - 180 Mils (160 Mils)
RECOMMENDED GAP 5 MM FFv PROBE	40 Mils	40 Mils
RECOMMENDED GAP 8 MM PROBE	50 Mils	50 Mils
RECOMMENDED GAP 11 MM PROBE	100 Mils	100 Mils