

	FFv™ PROBE TIP (5 mm diameter)	8 mm PROBE TIP	11 mm PROBE TIP	25 mm PROBE TIP
PRO Model Number	DP1009 Series	DP1001 Series	DP1007 Series	DP100851 Series
Bently® Model Number	3309 Series	33010 Series	3307 Series	3308 Series
Linear Range	10 to 70 mils (0.25 mm to 1.75 mm)	10 to 90 mils (0.25 mm to 2.30 mm)	20 to 180 mils (0.25 mm to 4.57 mm)	25 to 525 mils (0.635 mm to 13.33 mm)
System Lengths	1 m, 5 m, or 7 m	1 m, 5 m, or 9m	5 m or 9 m	5 m or 9 m
Sensitivity	200 mV/mil (7.87 V/mm)	200 mV/mil (7.87 V/mm)	100 mV/mil (3.94 V/mm)	20 mV/mil (0.787 V/mm)
Recommended Gap	40 mils	50 mils	100 mils	275 mils
Threaded Body Size	1/4-28 M8x1	3/8-24 M10x1	1/2-20 M14x1.5	1 1/4-12 M30x2
Common Applications	Steam turbines, pumps, gear boxes, motors, fans, general purpose	Steam turbines, pumps, gear boxes, motors, fans, general purpose	Hydro turbines, large displacement machines, general purpose	Axial thrust and differential expansion, general purpose
Eddy Current Field				