


	FFV PROBE TIP	8mm PROBE TIP	11mm PROBE TIP	25mm PROBE TIP
				
PRO Model Number	DP1009 Series	DP1001 Series	DP1007 Series	DP100851 Series
Bently® Model Number	3309 Series	33010 Series	3307 Series	3308 Series
Linear Range	10 to 70 mils (0.25mm to 1.75mm)	10 to 90 mils (0.25mm to 2.30mm)	20 to 180 mils (0.25mm to 4.57mm)	25 to 525 mils (0.635mm to 13.33mm)
System Lengths	5m or 7m	5m or 9m	5m or 9m	5m or 9m
Sensitivity	200 mV/mil (7.87 V/mm)	200 mV/mil (7.87 V/mm)	100 mV/mil (3.94 V/mm)	20 mV/mil (0.787 V/mm)
Recommended Gap	40 mils	50 mils	100 mils	275 mils
Threaded Body Size	1/4-28 M8x1	3/8-24 M10x1	1/2-20 M14x1.5	1 1/4-12 M30x2
Common Applications	Steam turbines, pumps, gear boxes, motors, fans, general purpose	Steam turbines, pumps, gear boxes, motors, fans, general purpose	Hydro turbines, large displacement machines, general purpose	Axial thrust and differential expansion, general purpose
Eddy Current Field	